

UBE Polyethylene V210

Polyethylene
UBE America, Inc.

Message:

UBE Polyethylene V210 is a Polyethylene material. It is available in North America for film extrusion.
Typical applications include:
Bags/Liners
Film

General Information			
Uses	Bags		
	Film		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR)	4.0	g/10 min	ASTM D1238
Vinyl Acetate Content	10.0	wt%	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	95		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	19.0	MPa	ASTM D638
Tensile Elongation (Break)	750	%	ASTM D638
Apparent Bending Modulus	80.0	MPa	ASTM D747
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	74.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT