

Syncure™ S1037B NATURAL

Crosslinked Polyethylene

PolyOne Corporation

Message:

Catalyst Masterbatch component for PolyOne's Syncure™ system, which is a two-step, silane-grafted, moisture-crosslinkable polyethylene system.

General Information			
Uses	Wire & Cable Applications		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm ³	ASTM D1505
Apparent Density ¹	0.48	g/cm ³	Internal Method
Melt Mass-Flow Rate (MFR) ² (190°C/2.16 kg)	8.7	g/10 min	ASTM D1238
NOTE			
1.	Geon® 1169		
2.	Procedure A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT