

SEQUEL® E3000FR

Thermoplastic Polyolefin Elastomer

LyondellBasell Industries

Message:

Sequel E3000FR thermoplastic olefinic elastomer (TPO) is designed for applications requiring stiffness and durability. This extrusion-grade material is specially formulated to exhibit improved flame resistance.

General Information	
Features	Durable
	Flame Retardant
	Good Stiffness
Uses	Automotive Interior Parts
	Industrial Applications
	Profiles
Processing Method	Extrusion
	Thermoforming

Physical	Nominal Value	Unit	Test Method
Density	1.26	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.5	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress ¹ (Yield)	21.0	MPa	ISO 527-2/50
Flexural Modulus	1600	MPa	ISO 178

NOTE	
1.	150x10x4 mm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT