

Nipoflex® 634

Ethylene Vinyl Acetate Copolymer

TOSOH Corporation

Message:

Nipoflex® 634 is an Ethylene Vinyl Acetate Copolymer (EVA) material. It is available in Asia Pacific, Europe, or North America for blown film, foam processing, injection molding, or sheet extrusion.

Important attributes of Nipoflex® 634 are:

- Clarity
- Copolymer
- Good Flexibility
- Good Weather Resistance
- High ESCR (Stress Crack Resistant)

Typical applications include:

- Caps/Lids/Closures
- Consumer Goods
- Film
- Labels

General Information			
Features	Copolymer		
	Good Flexibility		
	Good Weather Resistance		
	High Clarity		
	High Elasticity		
	High ESCR (Stress Crack Resist.)		
	High Gloss		
	High Impact Resistance		
Uses	Closures		
	Film		
	Labels		
	Lids		
	Toys		
Forms	Pellets		
Processing Method	Blown Film		
	Foam Processing		
	Injection Molding		
	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.949	g/cm ³	ASTM D1505
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	76.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

