

# LGE 422 LD

Expanded Polystyrene

LG Polymers India Pvt. Ltd.

Message:

Applications

Low Density blocks

General Information			
Features	Low density		
	Can foam		
Appearance	Translucent		
Forms	Sphere		
Physical	Nominal Value	Unit	Test Method
Density	0.0150 - 0.0300	g/cm <sup>3</sup>	ASTM D1505
Bead diameter	600.0 - 1000.0	μm	
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength	0.196 - 0.392	MPa	ASTM C203
Compressive Strength	0.0785 - 0.196	MPa	ASTM C165
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.029 - 0.034	W/m/K	ASTM C177

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT