

Sinvicomp DFR5806

Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp DFR5806 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of Sinvicomp DFR5806: Impact Resistant.

Typical application of Sinvicomp DFR5806: Foam

General Information			
Features	Good Impact Resistance		
Uses	Foam Profiles		
Forms	Powder		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.650	g/cm³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	220	MPa	ISO 178
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	79.0	°C	ASTM D1525
Heat Stability (180°C)	1.0	hr	ASTM D2115

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT