

Borealis PP TD210BF

Polypropylene Terpolymer

Borealis AG

Message:

TD210BF is a C2/C4 terpolymer

This grade is designed for sealing layers of oriented and non oriented films

CAS-No. 25895-47-0

General Information			
Additive	Antiblock		
Features	Med.-Wide Molecular Weight Distrib.		
	Recyclable Material		
Uses	Film		
	Food Packaging		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	130	°C	ISO 11357-3
Additional Information	Nominal Value	Unit	
Sealing Initial Temperature - 2 N	103	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT