

# Huaфон JF-A-WP1015

Polyurethane

Huaфон Group Co., Ltd.

## Message:

High Water Pressure Resistance PU Resin for Adhesive Layer

Characteristics

High water pressure resistance, good adhesive strength and nonstick surface.

Applications

Tents

General Information		
Features	Good Adhesion	
	Non-Stick	
Additional Information	Nominal Value	Unit
Solvents	DMF/TOL	
Uncured Properties	Nominal Value	Unit
Solids Content	34 to 36	%
Viscosity (25°C)	60 to 120	Pa·s
Cured Properties	Nominal Value	Unit
Tensile Modulus (100% Secant)	1.00 to 1.50	MPa
Tensile Strength	> 15.0	MPa
Tensile Elongation at Break	> 650	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT