

Vinylbond 96-1050-21 Black

Flexible Polyvinyl Chloride

Colorite Polymers

Message:

Vinylbond 96-1050-21 Black is a flexible vinyl extrusion compound formulated specially for the window market industry. This particular compound offers excellent bonding characteristics to ABS and PETG which makes it ideal for coextrusion applications.

General Information			
Features	Good flexibility		
Appearance	Black		
Forms	Particle		
Processing Method	Co-extrusion molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	69		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	15.7	MPa	ASTM D638
Tensile Elongation (Break)	490	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	49.9	kN/m	ASTM D624
Additional Information			

100% Modulus, ASTM D638: 860 psi

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

