

Premier HD05553

High Density Polyethylene

Premier Polymers, LLC.

Message:

Premier HD05553 ia a high density polyethylene copolymer suitable for injection molding applications. Meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact.

| General Information | | | |
|---|-------------------------|----------|-------------|
| Features | Copolymer | | |
| | Food Contact Acceptable | | |
| | High Density | | |
| Agency Ratings | FDA 21 CFR 177.1520 | | |
| Processing Method | Injection Molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 0.953 | g/cm³ | ASTM D1505 |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 5.5 | g/10 min | ASTM D1238 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT