

Europrene Lattice® 2620

Acrylonitrile Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Lattice 2620 is an aqueous anionic dispersion of an acrylonitrile-butadiene copolymer with low solid content obtained by emulsion polymerisation using rosin acid soap as emulsifier. It contains a non staining antioxidant.

Key Features

Europrene Lattice 2620 is used for solvent resistant technical goods.

Main Applications

Europrene Lattice 2620 is specifically designed to be used in the beater addition process.

General Information			
Additive	Antioxidation		
Features	Copolymer		
	Solvent resistance		
	Antioxidation		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	38.0	%	ASTM D5775
pH	10.5		ASTM D1417
Solids Content	35.0	wt%	ASTM D1417
Brokfield Viscosity ¹ (25°C)	30	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT