

NEXUS PE LDPE-1017

Low Density Polyethylene

Nexus Resin Group, LLC.

Message:

Low Density Polyethylene for coating applications

Nexus LDPE-1017 is designed for extrusion coating applications requiring high speed coating and good drawdown.

General Information			
Features	Fast Molding Cycle		
	Good Drawdown		
Uses	Coating Applications		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.917	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	10	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	9.31	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

