

Geon™ CPVC MC700

Chlorinated Polyvinyl Chloride

PolyOne Corporation

Message:

The Geon MC500 CPVC is an injection molding fittings compound for Industrial Pipe applications where enhanced resistance at elevated temperatures is needed. Geon MC500 demonstrates superior processability and excellent thermal stability.

General Information			
Uses	Industrial application		
	Accessories		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm ³	ASTM D792
PVC Cell Classification	23447		ASTM D1784
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	117		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	2990	MPa	ASTM D638
Tensile Strength (Yield, 23°C)	55.2	MPa	ASTM D638
Flexural Modulus	3380	MPa	ASTM D790
Flexural Strength (Yield)	103	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	96	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Annealed)	100	°C	ASTM D648
Injection	Nominal Value	Unit	
Processing (Melt) Temp	198 - 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT