

# MTEGRITY™ PP Impact Copolymer CP910

Polypropylene Impact Copolymer

M. Holland Company

Message:

MTEGRITY™ PP Impact Copolymer CP910 is a Polypropylene Impact Copolymer (PP Impact Copolymer) product. It can be processed by injection molding and is available in North America. Applications of MTEGRITY™ PP Impact Copolymer CP910 include containers, engineering/industrial parts and household applications.

Characteristics include:

- Antistatic
- Copolymer
- High Flow
- High Stiffness
- Nucleated

General Information			
Additive	Antistatic		
	Nucleating Agent		
	Slip		
Features	Antistatic		
	High Flow		
	High Stiffness		
	Impact Copolymer		
	Nucleated		
Uses	Slip		
	Containers		
	Household Goods		
Forms	Thin-walled Parts		
	Pellets		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	100	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.6	MPa	ASTM D638
Tensile Elongation (Yield)	5.0	%	ASTM D638
Flexural Modulus	1380	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	43	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

