

Fusabond® A560

Ethylene Acrylate Copolymer
DuPont Packaging & Industrial Polymers

Message:
DuPont™ Fusabond® A560 is a chemically modified ethylene acrylate copolymer

General Information			
Uses	Plastics Modification		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.930	g/cm³	ASTM D792, ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.6	g/10 min	ASTM D1238, ISO 1133
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	94.0	°C	ASTM D3418, ISO 3146
Additional Information	Nominal Value	Unit	
Maximum Processing Temperature	< 260	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT