

Gravi-Tech™ GRV-UR-110-W

Polyurethane
PolyOne Corporation

Message:

Gravi-Tech™ GRV-UR-110-W is a Polyurethane product. It can be processed by injection molding and is available in Asia Pacific. Applications of Gravi-Tech™ GRV-UR-110-W include industrial applications, medical/healthcare and sporting goods. Primary characteristic: non-toxic.

General Information			
Features	High Density		
	Non-Toxic		
Uses	Industrial Applications		
	Medical/Healthcare Applications		
	Projectiles		
	Radiation Shielding		
	Sporting Goods		
	Weighting & Balancing		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	11.0	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus ¹	276	MPa	ASTM D638
Tensile Strength ² (Yield)	2.62	MPa	ASTM D638
Tensile Elongation ³ (Break)	10	%	ASTM D638
Flexural Modulus	172	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 6.35 mm, Injection Molded)	160	J/m	ASTM D256A
Injection	Nominal Value	Unit	
Drying Temperature	65.6	°C	
Drying Time	4.0	hr	
Processing (Melt) Temp	182 to 204	°C	
NOTE			
1.	Type I, 5.1 mm/min		
2.	Type I, 5.1 mm/min		
3.	Type I, 5.1 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT