## Mirathane™ E155D

Thermoplastic Polyurethane Elastomer (Polyester)

Miracll Chemicals Co., Ltd.

## Message:

Mirathane $^{\text{M}}$  E155D is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Asia Pacific. Applications of Mirathane $^{\text{M}}$  E155D include coating applications, engineering/industrial parts, hose/tubing, additive/masterbatch and automotive.

Characteristics include:

Chemical Resistant

Good Flexibility

Puncture Resistant

Wear Resistant

General Information				
Features	Good Abrasion Resistance			
	Kink Resistant			
	Low Temperature Flexibility			
	Oil Resistant			
	Puncture Resistant			
	Solvent Resistant			
Uses	Automotive Applications			
	Belts/Belt Repair			
	Coating Applications			
	Compounding			
	Fabric Coatings			
	Film			
	Footwear			
	Hose			
	Overmolding			
	Seals			
	Sheet			
	Tubing			
	Wheels			
	Wire & Cable Applications			

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	97		
Shore D	55		
Mechanical	Nominal Value	Unit	Test Method

Abrasion Loss	35.0	mm³	DIN 53516
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	15.0 to 16.0	MPa	
300% Strain	28.0 to 38.0	MPa	
Tensile Strength (Yield)	38.0 to 43.0	MPa	ASTM D412
Tensile Elongation (Break)	340 to 380	%	ASTM D412
Tear Strength	160 to 170	kN/m	ASTM D624
Compression Set			ASTM D395
23°C, 72 hr	30	%	
70°C, 22 hr	55	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature <sup>1</sup>	-27.0	°C	ASTM D3417
NOTE			
1.	10°C/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

