# Tru-Bond<sup>™</sup> PB Gel

### Acrylic

Devcon

#### Message:

The Tru-Bond<sup>™</sup> Plastic Bonding Series of products provide UV/Visible light cured bonds to a wide range of plastics including ABS, polycarbonate, PET, PETG, flexible vinyls, urethanes and acrylics. The adhesive creates a flexible resilient polymer with outstanding impact resistance and flex. These products can also cure through most translucent substrates and UV blocked plastics.

General Information				
Features	Good Flexibility			
	High Impact Resistance			
	Resilient			
	UV Curable			
	ov curable			
Uses	Adhesives			
	Bonding			
	J			
Appearance	Clear/Transparent			
Forms	Gel			
Physical	Nominal Value	Unit	Test Method	
Water Absorption (24 hr)	5.1	%	ASTM D570	
VOC Content	< 1.0	%		
Non-Volatile Content	> 99	%		
Temperature Range	-54 to 149	°C		
Tensile Shear Adhesion				
Acrylic <sup>1</sup>	6.48	MPa		
PETG <sup>2</sup>	3.94	MPa		
Polycarbonate <sup>3</sup>	13.1	MPa		
Volume Shrinkage	8.8	%		
Linear Shrinkage	2.1	%		
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D)	37			
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	3.98	MPa		
Tensile Elongation (Break)	360	%	ASTM D638	
Films	Nominal Value	Unit	Test Method	
Elastic Modulus - MD	1.06	MPa	ASTM D882	
Optical	Nominal Value			
Refractive Index	1.500			
Clarity	> 98.0			
Thermoset	Nominal Value	Unit		

Shelf Life	100	wk
Uncured Properties	Nominal Value	Unit
Color	Amber	
Density	1.03	g/cm³
Flash Point	77.2	°C
NOTE		
1.	cohesive failure	
2.	substrate failure	
3.	substrate failure	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

