Hostacom CR 1171 G1A G14008

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hostacom CR 1171 G1A is a 12% talc filled PP copolymer, with medium melt flow rate, high impact resistance and excellent UV resistance. This grade is delivered in customer customized colors. This Data Sheet is giving general properties, some of them may be slightly altered upon color selected. For regulatory compliance information, see Hostacom CR 1171 G1A G14008 Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS). This grade is not intended for medical, pharmaceutical, food and drinking water applications.

| General Information | | | |
|--|-----------------------------------|-------------------|-------------|
| Filler / Reinforcement | Talc filler, 12% filler by weight | | |
| Features | Copolymer | | |
| | Impact resistance, high | | |
| | Good UV resistance | | |
| | Medium liquidity | | |
| | | | |
| Uses | Application in Automobile Field | | |
| | Car dashboard | | |
| Appearance | Available colors | | |
| Processing Method | Injection molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Density (23°C) | 0.990 | g/cm ³ | ISO 1183/A |
| Melt Mass-Flow Rate (MFR) (230°C/2.16 | | | |
| kg) | 13 | g/10 min | ISO 1133 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress (Yield, 23°C) | 21.0 | MPa | ISO 527-2 |
| Flexural Modulus ¹ (23°C) | 1800 | MPa | ISO 178/A |
| Flexural Stress ² (23°C) | 26.0 | MPa | ISO 178/A |
| Impact | Nominal Value | Unit | Test Method |
| Notched Izod Impact | | | ISO 180/1A |
| -30°C | 4.2 | kJ/m² | ISO 180/1A |
| 23°C | 20 | kJ/m² | ISO 180/1A |
| Thermal | Nominal Value | Unit | Test Method |
| Heat Deflection Temperature (1.8 MPa, Unannealed) | 54.0 | °C | ISO 75-2/A |
| Vicat Softening Temperature | 54.0 | °C | ISO 306/B |
| NOTE | | | |
| 1. | 1.0 mm/min | | |
| 2. | 1.0 mm/min | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

