Galloo GP-ABS-457

Acrylonitrile Butadiene Styrene Galloo Plastics S.A.

Message:

Black colored ABS compound

General Information			
Recycled Content	Yes		
Appearance	Black		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (220°C/	10.0		
kg)	40 - 50	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 30.0	MPa	ISO 527-2
Tensile Strain (Break)	> 7.0	%	ISO 527-2
Flexural Modulus	> 2000	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	> 5.0	kJ/m²	ISO 180

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

