

# POLIMAXX 291L

Expanded Polystyrene

IRPC Public Company Limited

## Message:

291L is a regular grade (Standard grade) Expandable Polystyrene (EPS) containing pentane as blowing agent. This grade is developed to meet the demand for fast molding cycles in vacuum machine. It is particularly well suited for the manufacturer of EPS insulation boards, block molded or product in continuous molding machine. This grade is also widely used for the production of low density decoration products and road construction blocks.

General Information		
Additive	Foaming agent	
Features	Foamable property	
	Fast molding cycle	
Uses	Insulating material	
Agency Ratings	EU 2002/95/EC	
RoHS Compliance	RoHS compliance	
Processing Method	Foam treatment	
Physical	Nominal Value	Unit
K-Value	56.0 - 58.0	
Minimum Density	13.0 - 14.0	kg/m <sup>3</sup>
Molded Density	14 - 25	g
Moisture		wt%
Bead diameter	0.800 - 1.60	mm
Blowing Agent - Pentane	> 6.0	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT