

TECHLEN H2302

Polypropylene
DAEHA Co., LTD

Message:

TECHLEN H2302 is a Polypropylene material filled with glass fiber. It is available in Asia Pacific. Primary attribute of TECHLEN H2302: High Stiffness.
Typical application of TECHLEN H2302: Automotive

General Information			
Filler / Reinforcement	Glass Fiber		
Features	High Stiffness		
Uses	Automotive Applications		
	Automotive Under the Hood		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.11	g/cm ³	ASTM D792

Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	120		ASTM D785

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	68.6	MPa	ASTM D638
Flexural Modulus	4120	MPa	ASTM D790

Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	98	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	145	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT