

Alkatuff® 488

Linear Low Density Polyethylene
Qenos Pty Ltd

Message:

Alkatuff® 488 is a Linear Low Density Polyethylene material. It is available in Asia Pacific for film extrusion.
Important attributes of Alkatuff® 488 are:
Antiblock
Slip
Typical application of Alkatuff® 488: Film


General Information			
Additive	Antiblock High Slip		
Features	Antiblocking High Slip		
Uses	Film		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.80	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT