

NEXT REGRIND PBT 420SEO-100RG

Polybutylene Terephthalate

NEXT Specialty Resins, Inc.

Message:

NEXT REGRIND PBT 420SEO-100RG is a Polybutylene Terephthalate (PBT) material filled with 30% glass fiber. It is available in North America.

Important attributes of NEXT REGRIND PBT 420SEO-100RG are:

Eco-Friendly/Green

Flame Retardant

Typical applications include:

Appliances

Electrical/Electronic Applications

General Information			
Filler / Reinforcement	Glass Fiber,30% Filler by Weight		
Recycled Content	Yes		
Features	Flame Retardant		
	General Purpose		
	Good Electrical Properties		
Uses	Appliances		
	Electrical/Electronic Applications		
	General Purpose		
Appearance	Natural Color		
Forms	Regrind		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	118		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	110	MPa	ASTM D638
Tensile Elongation (Break)	2.0	%	ASTM D638
Flexural Modulus	7240	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	204	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

