MTEGRITY™ ABS AB260

Acrylonitrile Butadiene Styrene

M. Holland Company

Message:

MTEGRITY™ ABS AB260 is an Acrylonitrile Butadiene Styrene (ABS) product. It is available in North America. Primary characteristic: impact resistant.

| General Information | | | |
|--|------------------------|-------------------|-------------|
| Features | High Impact Resistance | | |
| | Medium Flow | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.04 | g/cm ³ | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (220°C/10.0 | | | |
| kg) | 25 | g/10 min | ASTM D1238 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Yield) | 40.0 | MPa | ASTM D638 |
| Flexural Modulus | 1930 | MPa | ASTM D790 |
| Impact | Nominal Value | Unit | Test Method |
| Notched Izod Impact (23°C) | 350 | J/m | ASTM D256 |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (1.8 MPa, Unannealed) | 83.9 | °C | ASTM D648 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

