

# Generic PTFE - Glass Fiber

Polytetrafluoroethylene

Generic

## Message:

This data represents typical values that have been calculated from all products classified as: Generic PTFE - Glass Fiber  
This information is provided for comparative purposes only.

General Information			
Filler / Reinforcement	Glass Fiber		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.10 to 2.40	g/cm <sup>3</sup>	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	3560 to 4870	MPa	ASTM D638
Tensile Elongation (Break, 23°C)	100 to 370	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
CLTE - Flow	1.5E-5 to 9.4E-5	cm/cm/°C	ASTM D696

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

