

HANWHA CP-450

Polyvinyl Chloride Copolymer

Hanwha Chemical

Message:

Feature: High workability plasticity and thermal safety, High liquidity. Good for general glue.

Use: Paint, glue and ink.

General Information			
Features	Copolymer		
	Good Adhesion		
Uses	Adhesives		
	Paint		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.51 to 0.65	g/cm ³	ASTM D1895
Particle Size - 42Mesh(350µm) Sieve Pass %	100	%	Internal Method
Volatile Matter	< 4.0	%	ASTM D3030
Content - VAcM	13 to 15	%	Internal Method
Degree of Polymerization			
DP	500 to 600		JIS K6720-2
K-Value	53.0		DIN 53726

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT