

Vinnolit® E 68 SA

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

Message:

Vinnolit E 68 SA is a fine-particle paste-making emulsion homopolymer, classified as a low to medium viscosity resin. Plastisols made with Vinnolit E 68 SA exhibit a nearly newtonian rheology.

Vinnolit E 68 SA is recommended for the production of chemically blown foams. Typical applications are for example artificial leather cloth, floorings, unsupported foams and foamed wall-coverings.

| General Information | | | |
|---|-----------------------------|-------|-------------|
| Uses | Flooring | | |
| | Foam | | |
| | | | |
| Agency Ratings | EC 1907/2006 (REACH) | | |
| Processing Method | Plastisol | | |
| Physical | Nominal Value | Unit | Test Method |
| Apparent Density | 0.47 | g/cm³ | ISO 60 |
| K-Value | 68.0 | | ISO 1628-2 |
| Viscosity Number (Reduced Viscosity) | 116.0 | ml/g | ISO 1628 |
| Emulsifier Content | Medium | | |
| Particle Size Distribution ¹ | < 3.0 | % | ISO 4610 |
| Volatile Matter | < 0.30 | % | ISO 1269 |
| NOTE | | | |
| 1. | retained on 0.063 mm screen | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT