# NuSil MED10-6600

### Silicone

## NuSil Technology

#### Message:

NuSil Technology's restricted materials may be considered for use in short-term implant applications, 29 days or less, or for external applications. "Dispersion" is a term used to describe a silicone elastomer system that is suspended or dispersed in a solvent carrier. It is a complex solution that contains silicone polymers of various molecular weights and reinforcing fillers. The substituent groups comprising the polymer back bone structure may consist of the following: Polydimethylsiloxane, Dimethyl Diphenyl copolymer, and Fluoro homo polymer or copolymer. Silicone dispersions typically have low viscosities, which is beneficial for applications wherein a thin film coating is needed, and they can easily be used in dipping and spraying processes. NuSil uses a variety of solvents to disperse silicones, such as xylene, tert butyl acetate, heptane, hexane, acetone and naphtha. Comments: 1.46 R.I. IN XYLENE

General Information				
Filler / Reinforcement	Filler			
Features	Low Viscosity			
Uses	Coating Applications			
	Medical/Healthcare Applications			
Agency Ratings	USP Class VI			
Forms	Dispersion	Dispersion		
Processing Method	Dip Coating			
	Spraying			
Mechanical	Nominal Value	Unit		
Tensile Strength (300% Strain)				
-	2.24	MPa		
Optical	Nominal Value			
Refractive Index	1.460			
Thermoset	Nominal Value	Unit		
Thermoset Components				
Part A	Mix Ratio by Weight: 1.0			
Part B	Mix Ratio by Weight: 1.0			
Additional Information	Nominal Value	Unit		
Cure System	Platinum			
Uncured Properties	Nominal Value	Unit		
Density	1.10	g/cm³		
Viscosity	0.40	Pa·s		
Curing Time <sup>1</sup>	3.5	hr		
Pot Life (25°C)	1400	min		
Cured Properties	Nominal Value	Unit		
Shore Hardness (Shore A)	25			
Tensile Strength	8.27	MPa		
Tensile Elongation at Break	750	%		

Tear Strength	21.9	kN/m	
NOTE			
1.	30m/25°C + 45m/75°C 135m/150°C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

