

# Fixmaster Aluminum Putty

Epoxy; Epoxide

Loctite®

## Message:

Fixmaster Aluminum Putty is an Epoxy; Epoxide (Epoxy) product filled with aluminum. It is available in North America. Applications of Fixmaster Aluminum Putty include industrial applications and repairing material.

General Information			
Filler / Reinforcement	Aluminum		
Uses	Industrial Applications		
	Metal Repairing Material		
Appearance	Grey		
Forms	Pellets		
Hardness	Nominal Value	Test Method	
Durometer Hardness (Shore D)	85	ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.6	MPa	ASTM D638
Compressive Strength	68.9	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	107	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Volume: 1.0		
Resin	Mix Ratio by Volume: 6.0		
Pot Life (25°C)	20 to 30	min	
Demold Time (25°C)	180 to 240	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT