

Ablefilm ECF563

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablefilm ECF563 is an Epoxy; Epoxide (Epoxy) material filled with silver. It is available in North America. Primary attribute of Ablefilm ECF563: Conductive.
Typical applications include:
Adhesives/Tapes
Film

General Information			
Filler / Reinforcement	Silver		
Features	Electrically Conductive		
	Good Electrical Properties		
	Thermally Conductive		
Uses	Adhesives		
	Film		
Forms	Pellets		
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	1.9	W/m/K	ASTM C177
Thermoset	Nominal Value	Unit	
Pot Life (23°C)	120000	min	
Shelf Life (5°C)	26	wk	
Demold Time			
125°C	120	min	
150°C	30	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT