

Hanwha Total PP BJ750

Polypropylene Impact Copolymer

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

BJ750 is for injection molding application. STC impact copolymer shows an easy processability and an excellent stiffness combined with good impact strength & appearance.

Characteristics & Applications

Excellent balance between stiffness and impact strength

Good appearance (gas mark and void free, high gloss)

Good processability and productivity

Applications : Large E&E articles: Dish Washer Tub, W/M, & TWIM

General Information			
Features	Food Contact Acceptable		
	Good Impact Resistance		
	Good Processability		
	High Gloss		
	High Stiffness		
	Impact Copolymer		
Uses	Appliances		
	Electrical/Electronic Applications		
	Thin-walled Parts		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	28	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	90		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.4	MPa	ASTM D638
Tensile Elongation (Break)	> 100	%	ASTM D638
Flexural Modulus	1520	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C	39	J/m	
0°C	49	J/m	
23°C	78	J/m	

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	120	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT