Elastron® G G101.A65.B.E

Styrene Ethylene Butylene Styrene Block Copolymer

Elastron USA, Inc.

Message:

A soft, black SEBS based thermoplastic elastomer (TPE) compound that offers average physical properties and chemical resistance. Bondable to: PP, EVA, PE

General Information				
Features	Block Copolymer			
	Bondability			
	Good Chemical Resistance			
	Soft			
RoHS Compliance	RoHS Compliant			
Appearance	Black			
Forms	Pellets			
Processing Method	Extrusion			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.05	g/cm³	ASTM D792	
Molding Shrinkage			ASTM D955	
Flow	3.2	%		
Across Flow	1.3	%		
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	65		ASTM D2240	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress			ASTM D412	
100% Strain	2.00	MPa		
300% Strain	3.00	MPa		
Tensile Strength (Break)	6.00	MPa	ASTM D412	
Tensile Elongation (Break)	700	%	ASTM D412	
Tear Strength	31.0	kN/m	ASTM D624	
Compression Set			ASTM D395	
23°C, 22 hr	18	%		
70°C, 22 hr	62	%		
Injection	Nominal Value	Unit		
Suggested Max Regrind	20	%		
Rear Temperature	145 to 175	°C		
Middle Temperature	155 to 185	°C		

Front Temperature	160 to 190	°C	
Nozzle Temperature	175 to 205	°C	
Mold Temperature	25.0 to 50.0	°C	
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	150 to 170	°C	
Cylinder Zone 2 Temp.	155 to 175	°C	
Cylinder Zone 3 Temp.	165 to 185	°C	
Cylinder Zone 4 Temp.	175 to 205	°C	
Cylinder Zone 5 Temp.	180 to 210	°C	
Die Temperature	190 to 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

