

Etinox® ER-3102

Rigid Polyvinyl Chloride

Ercros, S.A.

Message:

Etinox® ER-3102 is a Rigid Polyvinyl Chloride product. It can be processed by extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary characteristic: flame rated.

General Information			
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.54	g/cm³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	39.2	MPa	ISO 527-2
Tensile Strain (Break)	110	%	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact Strength	4.9	kJ/m²	ISO 180
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	84.0	°C	ISO 306/B
Flammability	Nominal Value	Test Method	
Flame Rating	V-0	UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

