

POLYFLON™ D-210

Polytetrafluoroethylene

DAIKIN AMERICA, INC.

Message:

Daikin PTFE D-210 is a low PFOA content homopolymer polytetrafluoroethylene aqueous dispersion. D-210 has been designed for general purpose use in yarn coating, packing impregnation, glass fabric coating and release coating formulation applications.

General Information			
Features	Homopolymer		
Uses	Coating Applications		
	Wovens Coatings		
Appearance	White		
Forms	Liquid		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50 to 1.53	g/cm ³	Internal Method
pH (25°C)	8.5 to 10.5		ASTM D4441
Solids Content	59 to 61	%	ASTM D4441
Surfactant Content	6.0 to 7.2	%	ASTM D4441
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity (25°C)	35.0	cP	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT