

Sinpolene MBB1401

Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB1401 is a modified copolymer based black masterbatch designed specifically for use in injection moulding and extrusion of polyolefins, polystyrene and ABS. SINPOLENE MBB1401 has high pigment loading and thus offers high coloring value with superior quality and performance. SINPOLENE MBB1401 is delivered as free flowing pellets for processing convenience. It is packed in 25 kg bags. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Information	
Features	Recyclable materials
Uses	Composite
	Masterbatch
RoHS Compliance	RoHS compliance
Appearance	Black
Forms	Particle
Processing Method	Composite
	Injection molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	< 50	g/10 min	ASTM D1238
Carbon Black Content	> 40	%	ASTM D1603
Moisture Content		%	ASTM D3030

Additional Information
Recommended dosage: 1 - 3%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT