

PETILEN YY F 00756

High Density Polyethylene
PETKIM Petrokimya Holding A.S.

Message:

PETILEN YY F 00756 is a High Density Polyethylene product. It can be processed by film extrusion and is available in Asia Pacific, Europe, or North America. Applications of PETILEN YY F 00756 include bags/liners and film.

General Information			
Uses	Bags		
	Film		
	Heavy-duty Bags		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.949 to 0.954	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.050 to 0.090	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	> 600	hr	ASTM D1693
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	23.0	MPa	
Break	33.0	MPa	
Tensile Elongation (Break)	700	%	ASTM D638
Flexural Modulus	640	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	230	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT