

SolVin 264GC

Polyvinyl Chloride
INOVYN

Message:

Polyvinyl chloride made by suspension polymerisation.
APPLICATIONS:
Rigid profiles, pipes, flexible profiles, plasticised hoses, cable insulation and sheathing, plasticised film and sheet.
Crystal-clear articles.

General Information	
Features	High Clarity
	Semi Rigid
Uses	Cable Jacketing
	Film
	General Purpose
	Hose
	Piping
	Profiles
	Sheet
Processing Method	Calendering
	Extrusion

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.53	g/cm ³	ISO 60
K-Value	64.0		ISO 1628-2
Sieve Analysis			ISO 1624
Retained on 0.063 mm sieve	> 93	%	
Retained on 0.250 mm sieve	< 2.0	%	
Volatile Matter	< 0.30	%	ISO 1269
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 24538

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

