

ACRYLITE® Sheet Resist 45

Acrylic
Evonik Cyro LLC

Message:

Continuously manufactured ACRYLITE® Resist sheet is a versatile, thermoplastic material developed for the retail display and glazing markets as well as other markets requiring strength, appearance and weatherability.

High optical quality ACRYLITE® Resist sheet provides the beautiful look of acrylic with much greater impact strength for durability during manufacturing, shipping, and in-store use. Rigid, tough, and lightweight, ACRYLITE® Resist is easily fabricated and machined, including cutting, routing, forming, and cementing.

ACRYLITE® Resist is ideal for use in:

- P-O-P Displays
- Store Fixtures
- Glazing
- General Fabrication

General Information			
Features	Good Chemical Resistance		
	Good Toughness		
	Good Weather Resistance		
	High Impact Resistance		
	High Rigidity		
	Machinable		
Uses	Displays		
	Glazing		
Appearance	Clear/Transparent		
Forms	Sheet		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	ASTM D792
Water Absorption (23°C, 24 hr)	0.30	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	88		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2760	MPa	ASTM D638
Tensile Strength	59.3	MPa	ASTM D638
Tensile Elongation (Yield)	5.8	%	ASTM D638
Flexural Modulus	2550	MPa	ASTM D790
Flexural Strength	101	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	35	J/m	ASTM D256
Gardner Impact	2.26	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method

Deflection Temperature Under Load (1.8 MPa, Unannealed)	98.0	°C	ASTM D648
Vicat Softening Temperature	103	°C	ASTM D1525
CLTE - Flow	7.2E-5	cm/cm/°C	ASTM D696
Optical	Nominal Value	Unit	Test Method
Gardner Gloss (20°)	125		ASTM D523
Refractive Index	1.490		ASTM D542
Transmittance	91.6	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

