Amilan® CM2402

Polyamide 610

Toray Resin Company

Message:

Amilan® CM2402 is a Polyamide 610 (Nylon 610) product. It is available in Asia Pacific, Europe, or North America. Primary characteristic: good weather resistance.

| General Information | | | |
|------------------------------|-------------------------|-------|-------------|
| Features | Good Weather Resistance | | |
| Part Marking Code | >PA610< | | |
| Physical | Nominal Value | Unit | Test Method |
| Density (23°C) | 1.08 | g/cm³ | ISO 1183 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress (23°C) | 60.0 | MPa | ISO 527-2 |
| Tensile Strain (Break, 23°C) | 50 | % | ISO 527-2 |
| Flexural Modulus (23°C) | 2000 | MPa | ISO 178 |
| Flexural Stress (23°C) | 80.0 | MPa | ISO 178 |
| Thermal | Nominal Value | Unit | Test Method |
| Melting Temperature | 220 | °C | DSC |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

