

# INNOBATCH® PPH 6260

Polypropylene Homopolymer

Inno-Comp Ltd.

## Message:

INNOBATCH® PPH 6260 is a 60% chalk-filled polypropylene homopolymer based masterbatch. This grade is available in nature coloured form.

### Recommended application

These products that are offered under the brand name INNOBATCH® are recommended for the area of packaging materials, but they can be used for manufacturing household appliances and outdoor furniture and for other purposes as well.

The raw material having filler content is a semi-finished product from a user point of view; this allows the user to determine the optimal feeding rate during the processing operation.

General Information			
Filler / Reinforcement	Calcium Carbonate,60% Filler by Weight		
Features	Homopolymer		
Uses	Appliances		
	Furniture		
	Masterbatch		
	Packaging		
Appearance	Natural Color		
Forms	Pellets		
Resin ID (ISO 1043)	PP-H KD60		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.45	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0	g/10 min	ISO 1133
Ash Content (600°C)	53 to 63	%	ISO 3451-1A
Injection	Nominal Value	Unit	
Drying Temperature	80.0	°C	
Drying Time	2.0	hr	
Suggested Max Moisture	0.070	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT