

Xuchuan XCS-J130

Polyurethane

Xuchuan Chemical (Suzhou) Co., Ltd

Message:

Xuchuan XCS-J130 is a Polyurethane product. It can be processed by injection molding and is available in Asia Pacific. Primary characteristic: high hardness.

General Information		
Features	High Hardness	
Uses	Synthetic Leather	
Processing Method	Injection Molding	
Physical	Nominal Value	Unit
Solids Content	29 to 31	%
Viscosity (25°C)	100 to 140	Pa·s
Solvents	DMF, MEK	
Elastomers	Nominal Value	Unit
Tensile Stress (100% Strain)	12.7	MPa
Tensile Strength (Break)	12.7	MPa
Tensile Elongation (Break)	300	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT