

Evermore PUR UP-6042NR

Polyurethane (Polyester based)

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR UP-6042NR is a Polyurethane (Polyester based) (PUR-Ester) product. It is available in Asia Pacific. Applications of Evermore PUR UP-6042NR include coating applications and printing applications.

Characteristics include:

Good Flexibility

High Gloss

Moisture Resistant

General Information

Features	Aliphatic Good Flexibility High Gloss Moisture Resistant Soft
----------	---

Uses	Coating Applications Printing Ink
------	--------------------------------------

Elastomers	Nominal Value	Unit	Test Method
------------	---------------	------	-------------

Tensile Stress (100% Strain)	1.96 to 2.94	MPa	ASTM D412
------------------------------	--------------	-----	-----------

Tensile Strength (Yield)	> 9.81	MPa	ASTM D412
--------------------------	--------	-----	-----------

Tensile Elongation (Break)	> 500	%	ASTM D412
----------------------------	-------	---	-----------

Fill Analysis	Nominal Value	Unit	Test Method
---------------	---------------	------	-------------

Melt Viscosity (25.0°C)	< 0.500	Pa · s	ASTM D3835
-------------------------	---------	--------	------------

Additional Information	Nominal Value	Unit	Test Method
------------------------	---------------	------	-------------

Non-Volatile Content	37 to 39	%	
----------------------	----------	---	--

Solvents	H2O, DMAc		
----------	-----------	--	--

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

