

IROCOAT® CA-151HT

Thermoplastic Polyurethane Elastomer
Huntsman Corporation

Message:

IROCOAT®CA-151HT is a thermoplastic polyurethane elastomer product. It can be processed by coating and is available in North America. IROCOAT®CA-151HT application areas include glue/gummed paper and coating applications.

Features include:

- Strong adhesion
- Good flexibility
- chemical resistance
- Hydrolytic stability

General Information			
Features	Flexibility at low temperatures		
	Dispersible		
	Good adhesion		
	Good chemical resistance		
	Hydrolysis resistance		
	Hydrolysis stability		
Uses	Tape		
	Coating application		
RoHS Compliance	Contact manufacturer		
Forms	Particle		
Processing Method	Coating		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	80		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.4	MPa	ASTM D412
Tensile Elongation (Break)	35	%	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	79.0	°C	ASTM E1356
Additional Information			

Viscosity Range, 20 %: 200 to 400 cpsSolvent: MEKFunctionalized: Yes

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

