Unichem 5790

Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 5790 is a Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Asia Pacific, Europe, or North America.

General Information			
Features	General Purpose		
Uses	General Purpose		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.29	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	57		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant	3.28	МРа	ASTM D638
Tensile Strength	10.3	MPa	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

%

ASTM D638

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

450

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Tensile Elongation (Break)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

