Sylvin 2813-70 Grey 9524

Flexible Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 2813-70 Grey 9524 Is A Flexible Vinyl Compound Formulated With FDA Santioned Ingredients For Extrusion Applications.

General Information			
Features	Good Flexibility		
Agency Ratings	FDA Unspecified Rating		
Appearance	Grey		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.35	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	12.4	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	39.4	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	160 to 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

