

# SILMIX 68D2

Siloxane Polymer (UHMW)

SILON s.ro

### Message:

SILMIX 68D2 is a Silane blend, specially developed for the Spherisil P® -Process for Pipes.  
Clear liquid, composed of vinyltrimethoxysilane (VTMO), volatile and flammable, with characteristic smell.  
SILMIX 68D2 corresponds to the regulations of the European Union and the FDA (Food and Drug Administration, USA) for the production of products in contact with food stuffs.

General Information			
Features	Food Contact Acceptable		
Uses	Piping		
Agency Ratings	EU Food Contact, Unspecified Rating		
	FDA Food Contact, Unspecified Rating		
Appearance	Clear/Transparent		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Density <sup>1</sup>	0.970 to 0.980	g/cm <sup>3</sup>	DIN 51757
Viscosity (20°C)	1	mPa · s	DIN 51562
Boiling Point	120 to 122	°C	Internal Method
Flash Point	32	°C	DIN 51755-AP
Ignition Point <sup>2</sup>	205 to 210	°C	DIN 51562
NOTE			
1.	20°C		
2.	Open Cup		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT