

# Taipol 4270

Styrene Butadiene Styrene Block Copolymer

TSRC Corporation

## Message:

Taipol 4270 is a Styrene Butadiene Styrene Block Copolymer (SBS) product. It is available in Asia Pacific. Typical application: Adhesives/Tapes.

Characteristics include:

Good Processability

Low Viscosity

Stabilized

General Information			
Additive	Unspecified Stabilizer 2		
Features	Good Processability		
	Low Viscosity		
Uses	Adhesives		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.948	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	16 to 25	g/10 min	ASTM D1238
Bound Styrene	36.0 to 38.0	%	Internal Method
Ash Content	< 0.10	%	ASTM D5667
Gel Content	< 0.10	%	Internal Method
Volatiles	< 0.50	%	Internal Method
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	86		ASTM D2240
Optical	Nominal Value	Unit	Test Method
Yellowness Index	< 4.0	YI	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT