

SQUARE® LSR6013-30A/B

Silicone Rubber, LSR
Shenzhen SQUARE Silicone Co., Ltd.

Message:

Room Temperature Vulcanization Liquid Silicone Rubber

Product Description

The product is one kind of 2-part liquid silicone rubber, catalyzed by platinum, mixing ratio of parts A:B= 1:1, with low viscosity, cured under room temperature.

Key Features

Low viscosity,suitable for dispensing.

Cured in room temperature

Strong adhesion with silicone rubber.

High transparence

Applications

As the dispenser of silicone rubber surface,or used for bonder between silicone and silicone.

General Information			
Features	Low viscosity		
	Good adhesion		
	Definition, high		
	Room temperature vulcanization		
Uses	Bonding		
Appearance	Clear/transparent		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	30		ASTM D2240
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Component a	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by weight: 1.0		
Shelf Life	52	wk	
Uncured Properties	Nominal Value	Unit	Test Method
Viscosity			DIN 53019
-- 1	8.0	Pa·s	DIN 53019
-- 2	10	Pa·s	DIN 53019
Curing Time (80°C)	< 1.5	hr	
NOTE			
1.	Part B		
2.	Part A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

