Hanwha Total PP RB31D

Polypropylene

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

RB31D is a polypropylene compound and is a EPR modified material designed for automobile bumper facia. It features high-impact strength and weatherproof stability when used on automobile bumper facia.

In addition, this grade exhibits appropriate anti-heat levels, resistance to strain, and excellent processability. When formed, RB31D also features an improved external finish, superior size stability and peel resistance.

General Information			
Features	Good Processability		
	Good Surface Finish		
	Good Weather Resistance		
	High Impact Resistance		
	Low Temperature Impact Resistar	nce	
Uses	Automotive Bumper		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	7.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	6.0E-3 to 0.010	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	55		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	20.6	MPa	ASTM D638
Tensile Elongation (Break)	260	%	ASTM D638
Flexural Modulus	686	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-30°C	98	J/m	
23°C	No Break		
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45			
MPa, Unannealed)	85.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

